

REJILLAS IMPULSIÓN Y RETORNO

MODELO AC 101 • Impulsión/Retorno simple lama



Rejilla de lamas móviles horizontales de simple deflexión

Características del Modelo AC 101:

Ejecución:

- Aluminio extruido y anodizado o lacada en blanca.

H/L	P.V.P. COLOR ALUMINIO O BLANCO											
	200	250	300	350	400	450	500	600	700	800	900	1000
100	12,30	13,30	14,36	15,52	16,76	18,06	19,53	22,67	29,43	29,43	37,22	37,22
150	14,67	15,82	17,11	18,43	19,69	21,54	23,25	26,96	35,05	35,05	43,93	43,93
200	17,38	18,74	20,24	21,85	23,64	25,47	27,53	31,97	41,54	41,54	52,06	52,06
250	-	21,16	22,90	24,72	26,70	28,83	31,14	36,13	46,91	46,91	58,87	58,87
300	-	-	25,84	27,93	30,17	32,60	35,22	40,84	53,09	53,09	66,56	66,56
400	-	-	-	-	38,57	41,68	45,01	52,16	67,79	67,79	85,02	85,02
MODELO FALSO TECHO (595 x 595) P.V.P. 109,64												



REGULADOR DE CAUDAL
(Página 70)



LARGUEROS DE MONTAJE
(Página 70)

Superf. Libre d m ²	L x H (mm.)	qv (m ³ /h) 150	TABLA DE SELECCIÓN														
			200	300	400	500	700	900	1200	1500	3000	5000					
0.74	200 x 75	22 5.8 5.9 25 7.5 40	27 7.5	7.5													
1.1	300 x 75	- 4.1	19 5.5	28 8.2													
	200 x 100	3.8 10	5.0 18	7.6 40													
1.6	400 x 75	- 3.4	- 4.5	21 6.8	28 9.1												
	300 x 100	2.6 5	3.5 8	5.2 19	6.9 34												
2.4	600 x 75	- 3.7	- 5.6	20 7.4	25 9.3												
	400 x 100	2.3 4	34.5 8	4.6 15	5.8 23												
3.0	800 x 75	- 5.0	16 6.0	21 8.3	29 12												
	500 x 100	2.8 5	3.7 10	4.6 15	6.5 29												
4.0	1000 x 75	400 x 150	- 5.7	- 7.2	23 10	29 13											
	600 x 100	300 x 200	2.8 5	3.5 8	4.9 17	6.2 27											
4.9	1200 x 75	500 x 150	- 5.2	- 6.5	19 9.1	25 12	32 16										
	800 x 100	400 x 200	2.3 4	2.8 6	4.0 11	5.1 18	6.8 32										
6.0	1000 x 100	500 x 200	- 5.9	15 8.2	21 11	22 14	34 18										
	600 x 150	300 x 300	2.3 4	3.2 7	4.2 12	5.5 22	6.9 34										
7.8	1200 x 100	600 x 200	- 7.2	16 9.2	23 12	29 15											
	800 x 500	400 x 300	2.5 4	3.2 7	4.3 13	5.3 20											
10.5	1000 x 150	500 x 300	- 8.0	17 11	23 13												
	800 x 200	400 x 400	2.4 4	3.2 7	4.0 11												
13.2	1200 x 150	600 x 300	- 2.5	9.5 18	12 35	27											
	1000 x 200	500 x 400	4 3.2	7 6.3	30												
16.0	1200 x 200	600 x 400	- 2.1	9.5 15	12.5 31	24											
	800 x 300	500 x 500	3.0 2.6	5.0 5.1	18												
21.0	1000 x 300	600 x 500	- 11	26 15	38 -												
	800 x 400		2.0 2.8	4.0 11	6.9 32												
28.0	1200 x 300	800 x 500	- 9.0	20 18	33 30												
	100 x 400		- -	3.0 6	5.0 17												
35.0	1200 x 400			15 16.5	27 27												
	1000 x 500			2.4 4.1	4.0 11												
42.0	1200 x 500			- 15	24 25												
				2.0 2.8	3.3 7.5												

Nivel de ruido (db) Alcance del aire (m) Veloc. impulsión m/seg. Pérdida de carga (Pa)