

MODELO AC 123 • Reticulada



Rejilla reticulada de 12,5 x 12,5 mm.

Características del Modelo AC 123:

Ejecución:

- Aluminio extruido y anodizado o lacada en blanca.
- Superficie libre 90%.

P.V.P. MODELO AC 123										
H/L	200	250	300	350	400	450	500	600	700	800
100	18,65	21,32	23,38	26,02	27,42	30,48	31,99	36,43	45,05	45,05
150	21,04	24,48	26,63	29,69	32,10	35,30	37,93	42,50	53,92	53,92
200	25,01	29,04	32,23	35,78	38,82	42,67	45,95	51,99	65,60	65,60
250	-	33,12	37,05	40,85	45,05	49,23	53,03	61,12	76,90	76,90
300	-	-	41,73	47,10	50,51	56,25	59,80	68,66	86,42	86,42
400	-	-	-	-	59,02	65,22	71,70	82,51	105,20	105,20
500	-	-	-	-	-	-	87,43	99,49	127,81	127,81
600	-	-	-	-	-	-	-	124,02	152,69	152,69

PARA COLOR BLANCO INCREMENTAR 20%



REGULADOR DE CAUDAL
(Página 70)



LARGUEROS DE MONTAJE
(Página 70)

TABLA DE SELECCIÓN													
Superf. Libre d m ²	L x H (mm.)	qv (m ³ h) 150	200	300	400	500	600	800	1000	1200	1500	2000	2500
1.3	200 x 100	300 x 150	6 - 16	-	-	-	-	-	-	-	-	-	-
			3.2 3.30 4.2 5.7										
2.0	300 x 100		-	6 - 16	-	-	-	-	-	-	-	-	-
			2.1 1.5 2.7 2.2 4 5.1										
3.0	400 x 100		-	6 - 16	-	21	-	-	-	-	-	-	-
			1.9 1.2 2.7 2.4 3.6 4.2 4.6 6.6										
3.5	500 x 100		-	6 - 13	-	19	-	23	-	-	-	-	-
			2.3 1.65 3.2 3.3 4 5.1 4.7 6.9										
4.5	400 x 150		-	6 - 16	-	18	-	25	-	-	-	-	-
	300 x 200		-	2.5 1.98 5.1 3 3.7 4.2 4.8 7.2									
6.0	500 x 150		-	6 - 12	-	19	-	25	-	-	-	-	-
			-	2.4 1.8 2.7 2.4 3.7 4.2 4.6 6.6									
7.5	500 x 150		-	6 - 15	-	20	-	24	-	-	-	-	-
			-	2.2 1.5 3 3 3.7 4.2 4.4 6									
9.3	600 x 200		-	9 - 16	-	19	-	26	-	-	-	-	-
			-	2.4 1.8 3 3 3.5 3.9 4.6 6.6									
12.5	800 x 200		-	6 - 13	-	19	-	26	-	-	-	-	-
			-	2.2 1.5 2.6 2.3 3.3 3.3 4.4 6									
17.5	500 x 400		-	6 - 13	-	19	-	25	-	-	-	-	-
	1000 x 1000		-	1.9 1.14 2.4 1.8 3.2 3.3 3.9 4.8									
22.0			-	6 - 15	-	20	-	20	-	-	-	-	-
			-	1.9 1.14 2.5 1.98 3.2 3.3									

Nivel de ruido (db) Alcance del aire (m) Veloc. impulsión m/seg. Pérdida de carga (Pa)