

REJILLAS LINEALES Y RETÍCULAS

MODELO AC 440 • Lineales



Rejilla lineal de lamas fijas para impulsión o retorno

Características del Modelo AC 440:

- Ejecución:
- Aluminio extruido y anodizado.
 - Montaje en pared, techo o alfeizar.

P.V.P. MODELO AC 440												
H/L	200	250	300	350	400	450	500	600	700	800	900	1000
75	22,72	22,72	25,69	25,69	25,69	28,77	28,77	31,43	38,21	38,21	42,19	42,19
100	24,74	24,74	28,10	28,10	28,10	31,28	31,28	35,26	45,21	45,21	51,60	51,60
125	26,75	26,75	30,70	30,70	30,70	34,51	34,51	39,79	52,80	52,80	60,81	60,81
150	30,81	30,81	36,31	36,31	36,31	42,04	42,04	48,02	63,66	63,66	73,39	73,39
200	37,42	37,42	44,71	44,71	44,71	52,11	52,11	60,07	80,17	80,17	92,62	92,62
250	-	43,38	51,16	51,16	51,16	58,93	58,93	69,06	95,56	95,56	111,85	111,85
300	-	-	57,70	57,70	57,70	64,40	64,40	77,30	104,55	104,55	115,80	115,80

PARA COLOR BLANCO INCREMENTAR 20%



REGULADOR DE CAUDAL
(Página 70)



LARGUEROS DE MONTAJE
(Página 70)

Superf. Libre d m ²	L x H (mm.)	qv (m ³ /h) 150	TABLA DE SELECCIÓN																	
			200	300	400	500	700	900	1200	1500	3000	5000								
0.8	300 x 70	200 x 100	15	4	25	9														
			3.5	8.6	7.0	35														
1.2	400 x 75	300 x 100	-	3	20	8	25	12												
	200 x 150		2.3	4	4.8	16	7.0	35												
1.8	600 x 75	400 x 100			15	6	20	9	25	12										
	300 x 150	200 x 200			3.0	6.3	4.5	15	6.0	25										
2.2	800 x 75	500 x 100			15	6	20	9	25	12	30	17								
					2.5	4.4	3.7	10	5.0	17	7.5	40								
2.9	1000 x 75	600 x 100				7	20	10	25	15	30	17								
	400 x 150	300 x 200				2.8	6	3.7	10	5.8	23	6.0	25							
3.6	1200 x 75	800 x 100						20	9	25	13	25	16							
	500 x 150	400 x 400						3.0	6.3	4.5	15	5.0	17							
4.4	1000 x 100	600 x 150						15	8	20	12	20	14	30	20					
	500 x 200	300 x 300						2.5	4.4	3.7	10	3.7	10	6.3	28					
5.7	1200 x 100	800 x 150							15	10	15	12	25	18						
	600 x 200	400 x 300							2.9	6.1	3.0	6.3	4.8	16						
7.7	1000 x 150	800 x 200							-	9	-	11	20	15	31	17				
	500 x 300	400 x 400							2.2	3.5	2.3	4	3.7	10	5.5	22				
9.7	1200 x 150	1000 x 200								15	13	27	16	30	27					
	600 x 300	500 x 400								2.8	6	4.2	14	5.8	23					
11.7	1200 x 200	800 x 200								15	13	23	14	30	19	34	23			
	600 x 400									2.3	4	3.5	8.8	4.8	16	5.9	25			
15.4	1000 x 300	800 x 400											18	12	25	16	29	20	30	33
														2.7	5.0	3.7	10	4.5	15	5.5
20.5	1200 x 300	1000 x 400												19	14	24	18	27	21	
															2.7	5.0	3.4	8.0	4.0	11.3

Nivel de ruido (db) Alcance del aire (m) Veloc. impulsión m/seg. Pérdida de carga (Pa)